

## PROVA-100 4-20mA LOOP CALIBRATOR



### FEATURES

- 4-20mA, with 1  $\mu$  A resolution
- Basic Accuracy 0.025% + 5  $\mu$  A
- Auto-Ramp and Easy Step Functions
- 1-100% Input
- 0-20mA, 0-24mA Selectable
- Easy Just-Type-in Number Operation



### SPECIFICATION

#### Electrical Specification

Range	Resolution	Accuracy
0-4 mA	0.001mA	0.025% + 10 $\mu$ A
4-20 mA	0.001mA	0.025% + 5 $\mu$ A
20-24 mA	0.001mA	0.025% + 5 $\mu$ A

#### General Specification

<b>Battery Type</b>	9V Alkaline Battery (External Power Input 9-15V)
<b>Display</b>	4+5 Digits
<b>Operating Temperature</b>	0 to 50 °C (32 to 122 °F )
<b>Operating Humidity</b>	Less than 85% relative
<b>Storage Temperature</b>	-20 to 60 °C (-4 to 140 °F )
<b>Dimension</b>	88 x 168 x 26 mm (3.46" x 6.61" x 1.03")
<b>Weight</b>	330 g / 11.63 oz
<b>Accessories</b>	Carrying case x 1 ; Users Manual x 1 External Battery Pack (without batteries) 9V battery x 1 ; Test leads x 1 ; Alligator clip x 1