

LX-10A



Features:

- Data Hold
- Auto Power Off (APO)
- Max./Min.

Technical Data

Basic Function	LX-10A	Resolution	Accuracy
Illumination	Lux 0~9999 Lux	1 Lux	±4% rdg +8% dgts.
	Lux ≥ 10000 Lux	10 Lux	±5% rdg +10% dgts.
Range	0~199,999 Lux		
Sensor Type	Silicon photocell		
Power	AAA 1.5V x 3		
Standard Accessories	Soft Carrying Case, Manual		
Dimension	160(H) x 50(W) x 28(D)mm		

SL-13A



Features:

- Data Hold
- Auto Power Off (APO)
- Max./Min.
- Overload Indication "UN & OL"

Technical Data

Basic Function	SL-13A	Resolution	Accuracy
Sound Level	30~130dB	0.1dB	±1.5dB
Sampling Time	Fast / Slow		
Frequency	31.5 Hz~8KHz		
Sensor Type	1/2 inch Condenser Micro Phone		
Power	AAA 1.5V x 3		
Standard Accessories	Soft Carrying Case, Manual		
Dimension	150(H) x 52(W) x 27(D)mm		

AVM-03



Features:

- Used for Temperature, Wind Speed & Wind Chill Notification.
- Data Holder
- Auto Power off. (APO)
- Back Light.

Technical Data

Basic Function	AVM-03	Resolution	Accuracy
Wind Speed	0~30m/s (as standard)	0.1m/s	±5% rdg +0.5 dgts.
	1.4~108 Km/h (Refer Only)		±5% rdg +15 dgts.
	0.7~58 Knots (Refer Only)		±5% rdg +10 dgts.
	0.8~7 mph (Refer Only)		±5% rdg +10 dgts.
	78~5905 ft/min (Refer Only)		±5% rdg +180 dgts.
Temperature	-10~50°C	0.1°C	±2°C
	14~122°F		±4°F
Power	AAA 1.5V x 3		
Standard Accessories	Hard Carrying Case, Manual		
Dimension	160(H) x 50(W) x 28(D)mm		

HD-303



Features:

- Max./Min.
- Data hold
- Unit Selectable °C / °F
- Back Light
- Auto Power off (APO)

Technical Data

Basic Function	HD-303	Resolution	Accuracy
Humidity	% 0~100%RH	0.1%RH	±5%RH
Temperature	°C -10~60°C	0.1°C	±1.0°C
	°F 14~140°F		
Sampling Rate	1/s		
Power	AAA 1.5V x 3		
Standard Accessories	Hard Carrying Case, Manual		
Dimension	155(H) x 50(W) x 28(D)mm		

